Material Safety Data Sheet Omni Specialty Packaging For Compliance with OSHA 29 CFR 1910.1200 and ANSI Z400.1-1998

Packaged for Stihl Incorporated, 536 Viking Drive, Virginia Beach, VA 23452

1. Product and Company Identification						
Product Name	MSDS Code Number					
STIHL 2-CYCLE HP ENGINE OIL						
PART NUMBER; 0781-319-8008 (2.6 _{oz}); 0781-319- 8051 (5.2oz);						
0781-319-8009 (6.4oz); 0781-319-8010 (12.8 oz); 0781-319- 8021 (1Gal); 0781-319- 8044 (5 Gal); 0781-319-8045 (55 Gal)						
Trade Name & Synonyms	Date of Last Revision					
rade Name & Synonyms	01/02/2009					
	01/02/2009					
Chemical Name	Manufacturer					
	Omni Specialty Packaging					
C.A.S. Number	Address					
	10399 Hwy. 1 South Shreveport, La. 71115					
Grades or Minor Variant Identities	Information Telephone Number					
	(318) 524-1100					
	Foreign Emergency Telephone Number					
Product Use (for Canada)	Emergency Telephone Number					
	(318) 524-1100					

2. Composition/Information on Ingredients					
Hazardous Components	C.A.S Number	Exposure Limits Oil Mist	%		
Petroleum Distillates, Hydrotreated Heavy Paraffinic	64742-54-7	5 mg/m ³	Blend		
Petroleum Distillates, Solvent Dewaxed heavy Paraffinic	64742-65-0	5 mg/m ³	Blend		
Residual Oils (petroleum). Solvent Dewaxed	64742-62-7	5 mg/m ³	Blend		
RESIDUAL Oils (petroleum), Hydrotreated	64742-57-0	5 mg/m ³	Blend		
Stoddard Solvent	8052-41-3	525 mg/m ³	8		
Additive Package	Mixture	N/A	< 7		
Dye	Mixture	N/A	0.14		
OSHA Regulatory Status 29 CFR 1910.1200.					

3. Hazards Identification

This produc	t is considered not hazardous under 29 CFR 1910.1200 (Hazard	Communication).			
Routes of Exposure	Signs and Symptoms	Single, Repeated, or Lifetime Exposures	Severity (Mild, Moderate, Severe)	Acute and Chronic Health Effect(s)	Target Organ(s)
Eye	Practically non- irritating to the eye upon direct contact.				
Skin	Minimally irritating upon direct contact.	May cause irritation/dermatitis.			
Inhalation	Low hazard at standard temperatures and pressures. Inhalation of oil mist or fumes can cause irritation of the nose, throat and upper respiratory tract				
Ingestion	Don not ingest. May cause nausea, vomiting/diarrhea.				
Other	On rare occasions, prolonged and repeated exposure to oil				

MSDS – OMNI SPECIALTY PACKAGING

mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations.		
Medical Conditions Aggravated by Exposure		

Personnel with pre-existing skin disorders should avoid contact with this product.

4. First Aid Measures Routes of Exposure First Aid Instructions Immediate Medical Attention Delayed Eye Flush with large amount of water for 15 minutes. Get medical attention if eye irritation develops or persists. Skin Wash with soap and water. Remove contaminated clothes and wash before reuse. Get medical attention if skin discolor develop. Inhalation This material is not expected to present an inhalation exposure at ambient conditions Ingestion Do not induce vomiting. Get immediate medical attention or advice. Other Not available Note to Physicians (Treatment, Testing, and Monitoring)

Not available

Flashpoint				5. Fire Fighti	ing Measur	es		
Method:	۴	Flammable (Exp LEL	olosive) L	imits in Air UEL	Autoignition Temperature	°F	Hazard ra	ating
РМСС	170	Not determine	d	Not determined	N/A	N/A	Fire	1
lame Propagation o	or Burnin	g Rate	Proper	ties Contributing to Fire	Flammability		Health	0
(for solids)			Intensi	ſy	Classification		reactivity	0
Not Available			Not D	etermined	Not Available			
Extinguishing Media			Extinguishing Media to Avoid				Reactions to Extinguishi	ng Media
Water for, foam, C	CO2, dry	/ chemical	Not Available				Not Available	
Protection and Proce	edures fo	or Firefighters						
Wear positive pres protective clothing					e water to cool co	ontainers expose	ed to flames. Structural fire	fighters'
Unusual Fire and Exp	plosion	Hazards						
fist or sprays may	, y be fla	mmable below t	the proc	luct normal flash point.				

6. Accidental Release Measures

Spill/Leak Clean-up Procedures and Equipment

Observing health hazards described above, ventilate area. Dike to contain spill. Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material. Keep from sewers and natural water.

Evacuation Procedures

* Consider initial downwind evacuate for at least 300 meters (1000 feet).

Fire

* If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Special Instructions

When using this material, do not eat, drink, or smoke. Wash thoroughly after handling. Keep away from animals and children.

Reporting Requirements

Spills that enter a water body must be reported immediately to the USEPA's National Response Center at (800)546-2972. Check with your local and state regulators regarding their reporting requirements.

7. Handling and Storage

Handling Practices and Warnings

Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids.

Storage Practices and Warnings

Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product

MSDS – OMNI SPECIALTY PACKAGING

residue (liquid, and/or va	por) and can be dangerous.					
8. Exposure Control/Personal Protection						
Other Engineering controls	Ventilation					
N/A	Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended limits.					
Routes of Entry:	Personal Protective Equipment (PPE) for Normal Use:	PPE for Emergencies				
Eye/Face	Safety glasses or face shield where splashing is possible.	Full face shield				
Skin	As needed to prevent repeated skin contact. Solvent resistant gloves should be used if needed.					
Inhalation	Not normally needed.	Respirator				

9. Physical and Chemical Properties						
Appearance Blue Liquid				Odor Mild petroleum odor		
Normal Physical State:			Boiling Point	N/A ° F		
X Liquid		Gas	Melting Point	N/A ° F		
Solid		(Other)	Freezing Point	0 ° F		
Specific Gravity or Density $(H_2 0 = 1)$		Solubility in Water		рН		
0.87		Negligible		N/A		
Vapor Pressure (mm Hg.)		Vapor Density (AIR = 1)		Evaporation Rate (Butyl Acetate = 1)		
<0.01		Not Determined		Not Available		
Other						
N/A						

10. Stability and Reactivity						
Hazardous Products Produced During Decomposition Combustion products may include smoke, fumes, oxides of phosphorus, boron, sulfur, nitrogen, carbon dioxide, carbon monoxide, and other low molecular weight hydrocarbons.						
Hazardous Polymerization? May Occur X Will Not Occur Conditions to Avoid						
Conditions to Avoid Sources of ignition						

11.	Toxice	ological	Information
-----	--------	----------	-------------

Toxicity Data, Epidemiology Studies, Carcinogenicity, Neurological Effects, Genetic Effects, Reproductive Effects, or Structure Activity Data

Acute Toxicity: Test on similar materials show a low order of acute oral and dermal toxicity.

Acute Oral Effects: Test on similar materials indicates low order of acute toxicity.

Acute Inhalation Effects: Low acute toxicity expected on inhalation.

Skin Effects: Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies. **Eye Irritation**: Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on similar products.

Carcinogenicity:

Skin: Not considered a potential carcinogen base on IP346 DMSO of less tan 3.0 wt%

Genotoxicity: This product is considered non-mutagenic and has negative potential for tumor development based on from Modified Ames Assay, with Mutagenic Index of less than 1.0.

12. Ecological Information

Toxicity, Environmental Fate, Physical/Chemical Data, or Other Data Supporting Environmental Hazard Statements

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

13. Disposal Considerations

Regulations

Dispose in accordance with all local, state, and federal regulations. Keep this product out of sewers and waterways.

Note: State or local requirements may differ from federal regulations. Processing or using this product may make the information here inappropriate. Waste generators are responsible for waste classification, transport, and disposal.

14. Transport Information							
Regulated for shipping? Proper Shipping Name Packing Group							
🗌 Yes X No				N/A	N/A		
Do changes in quantity, packaging, or shipment method change product qualification?				Hazard Class	Identification Number		
🗌 Yes x No			No	N/A	N/A		
Other	Other						
N/A	N/A						

	15. Regulatory Information				
Federal Regulations	s (OSHA, TSCA, CERCLA, FIFRA, EPCRA, CAA, CWA, SDWA, CPSA, DEA, FDA/USDA, etc.)				
State Regulations					
U.S. Federal Regu	latory Information:				
(40 CFR 355 App 311/312 Categories: (40 CFR 370) 313 Categories: Clean Air Act: Clean Water Act: (40 CFR 116; 44 OSHA (29 CFR 1910 RCRA (40 CFR 261.) EPA/TSCA Inventory State Regulations California Prop 65 Florida	 Immediate (Acute) Health Effects No Delayed (Chronic) Health Effects No Fire Hazard No Sudden Release of Pressure Hazard No Reactivity Hazard No Toxic Chemicals (40 CFR 372) No Hazardous Air Pollutants (HAPS) No If spilled into navigable waters it is reportable to National Response Center, 800-424-8802 D1.15) Reportable Quantity = Oil Sheen present on navigable water surface This product is not hazardous under Hazard Communication Standard 29 CFR 1910.1200 This product does not meet hazardous waste criteria. * The components of this product are listed on the EPA/TSCA inventory of chemicals. CAS No. 64742-54-7 				
Pennsylvania RTK Illinois DOL TSL	Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%. No listed ingredients are present				
Other Regulations WHMIS (Canada) CONEG Metals: CONEG Metals regul EEC (Europe):	s: Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant with Controlled Products Regulation Since cadmium, chromium, lead and mercury are not detectable and it does not exceed 100 ppm total in this product, it is compliant with				
International Regula	itions				
N/A					
•					
Other					
N/A					

16. Other Information

Label Text, Hazard Rating System, Key Legend, or Other

Abbreviations

ACGIH(American Conference of Governmental Industrial Hygienists); ANSI(American National Standards Institute); CAS(Chemical Abstract Service); CERCLA(Comprehensive Environmental Response, Compensation, & Liability Act); CFR(Code of Federal Regulations); CHIP (Chemicals Hazard Information & Packaging for Supply); CONCAWE (European Organization for Environment, Health & Safety); CPR(Controlled Products Regulations); DOL (Department of Labor); EED(European Economic Community Directives); EINECS (European Inventory of Existing Commercial Chemical Substances); EL50 (Effective loading rate required to immobilize 50% invertebrate species); ELINCS(European List of New Chemical Substances); EPA (Environmental Protection Agency); EPCRA(Emergency Planning & Community Right-To-Know Act of 1986); EU(European Union); FDA(Food & Drug Administration-USA); GHS (Global Harmonization System); HCS (Hazard Communication Standard); IARC(International Agency for Research on Cancer); ILO(International Labor Organization); LC50(Lethal Concentration 50% test organisms); LD50(Lethal Dose 50% test organisms); LVP-VOC(Low Vapor Pressure Volatile Organic Compound); MSDS(Material Safety Data Sheet); MSHA(Mine Safety & Health Administration); NIOSH(National Institute of Occupational Safety & Health);NTP(National Toxicology Program); OSHA(Occupational Safety & Health Administration); RICSH(National Institute of Occupational Safety & Health);NTP(National Toxicology Program); OSHA(Occupational Safety & Health Administration); RICHermissible Exposure Limit); Prop 65(California Proposition 65); PMCC(Pensky Martin Closed Cup); RCRA(Resource Conservation & Recovery Act); RTK(Right-To-Know); R-Phrases(EU Risk Phrases; S-Phrases (EU Safety Phrases); SARA(Superfund Amendments & Reauthorization Act); TSCA (Toxic Substances Control Act); TSL (Toxic Substance List); TLV(Threshold Limit Value); WHMIS(Workplace Hazardous Materials Information System-Canada); IL50 (Inhibitory loading rate required to reduce algal growth rate by 50%; IbL50 (Inhibitory loadin

NFPA Hazard Rating	– Health -Fire	0 Slight 1 Slight	
Prepared By:	Reactivity Juan Parker		(318) 524-1100

This MSDS complies with OSHA Hazard Communication Standard (HCS) 29 CFR 1910.1200 and conforms to ANSI Z 400.1 16-Section Format.

Disclaimer: Omni Specialty Packaging believes this information is accurate but not all-inclusive in all circumstances. It is the responsibility of the user to determine suitability of the material for their purposes. No warranty, expressed or implied, is given.

NOTE: OSHA's Hazard Communication Standard (29 CFR 1910.1200) does not require the information requested in Sections 11, 12, 13, 4, 15, and 16 for MSDSs. If your company chooses not to fill in these sections, you may wish to enter something (like N/R for "not regulated" or N/A for "not applicable") to indicate that the field is purposely being left blank.