Aervoe 8178 EPS Foam / Concrete Adhesive - Aerosol



Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

This MSDS covers the following Aervoe aerosol product

PRODUCT NAME: 8178 EPS Foam / Concrete Adhesive

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe Industries Inc.

ADDRESS: 1198 Mark Circle. Gardnerville. NV 89410

DATE REVISED: November 24, 2008 REASON REVISED: Updated

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	OSHA PEL	ACGIH TLV	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Naphthol Spirits (CAS 8052-41-3)	500 ppm	100 ppm	N / AV	N / AV
*Hexane (CAS 110-54-3)	500 ppm	50 ppm (skin)	2870 mg / kg (Rat-Oral)	N / AV
*Cyclohexane (CAS 110-82-7)	300 ppm	300 ppm	> 5 g / kg (Rat-Oral)	N / AV
Dimethyl Ether Propellant (CAS 115-10-6)	N / AV	1000 ppm	N / AV	164,000 ppm / 4 hr (Rat-Inha)

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N / AP = Not Applicable N / AV = Not Available

C8178 EPS Foam / Concrete Adhesive (aerosol)

8178MA

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: N / AP SPECIFIC GRAVITY (H20=1): 0.8 g/mL (concentrate) VAPOR DENSITY: Heavier than air

SOLUBILITY IN WATER: Negligible EVAPORATION RATE: Faster than n-Butyl Acetate

APPEARANCE AND ODOR: Clear or blue liquid with solvent odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: < 0° F (-18° C) METHOD USED: Estimated FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 0.7% UPPER: 18.0%

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical, Water Spray or Fog

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to heat or fire to prevent pressure build up.

Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Treat as cylinders of compressed gas.

Closed containers may rupture due to pressure build up from extreme heat or fire. FLAMMABILITY: Flammable aerosol under conditions of sparks, flame, or hot surfaces.

SENSITIVITY TO IMPACT: Aerosol cans are under pressure. Product will be expelled rapidly if container is punctured.

SENSITIVITY TO STATIC DISCHARGE: Primarily vapors

SECTION V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: Open flame, welding arcs, heat, sparks.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Dioxide, Carbon Monoxide, Hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION: High concentrations of vapors may irritate nose and throat and cause symptoms of

intoxication such as dizziness, nausea, headache, or indigestion. **SKIN CONTACT:** May cause irritation due to defatting of skin.

EYE CONTACT: Direct spray or vapors will irritate and may harm eyes.

INGESTION: Not likely in normal use but swallowing large amounts may be harmful.

CARCINOGENICITY: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

TERATOGENICITY: Not established MUTAGENICITY: Not established MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: None known.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.

SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.

EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

INGESTION - Do NOT induce vomiting, seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame. Keep out of reach of children.

OTHER PRECAUTIONS: Do not smoke while using this product. Read label precautions carefully. Follow label directions to avoid injury.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.

VENTILATION: General ventilation to maintain exposure limits below TLV's as defined in Section II.

PROTECTIVE GLOVES: Chemical resistant gloves such as Neoprene or Nitrile rubber.

EYE PROTECTION: Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK / HYGIENIC PRACTICES: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.