

1. Identification

Product Identification

Product Identifier: SET
Recommended Use: SET Epoxy Adhesive is a high-strength, anchoring adhesive.
Use Restrictions: To ensure proper installation use according to package directions, complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
 Pleasanton, CA 94588
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada)
 1-352-323-3500 (International)

For most current SDS, please visit our website at www.strongtie.com/sds

2. Hazard Identification

General Information

SET Epoxy Adhesive is a high-strength, non-shrink, epoxy adhesive for anchoring doweling threaded rod and rebar. It is a two-part (1:1) system packaged as a single unit in a dual cartridge. The two parts of this product have been individually assessed according to the Globally Harmonized System (GHS). Exposure to the individual components will only occur with improper use. The resin and hardener are dispensed and mixed simultaneously through the mixing nozzle. The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. The final cured product will be uniformly light gray in color and can be considered nonhazardous. Some hazards may apply upon grinding or cutting through hardened product. This Safety Data Sheet covers the hazards and responses for the safe use of this product.

Resin (White Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Skin Corrosion/Irritation	Category 2	H315: Causes skin irritation
	Serious Eye Damage/Irritation	Category 2	H319: Causes serious eye irritation
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
	Germ Cell Mutagenicity	Category 2	H341: Suspected of causing genetic defect
Environmental Hazards:	Carcinogenicity	Category 2	H351: Suspected of causing cancer
	Chronic Aquatic Hazard	Category 2	H411: Toxic to aquatic life with long lasting effects

Main Symptoms: Irritation of eyes and skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin. Long term exposure may cause chronic effects.

GHS Label Elements



Contains: Resins, Butyl Glycidyl Ether, Titanium Dioxide
Signal Word: **WARNING!**
Hazard Statements:
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H317: May cause an allergic skin reaction.
 H341: Suspected of causing genetic defects.
 H351: Suspected of causing cancer.
 H411: Toxic to aquatic life with long lasting effects.
Precautionary Statements:
Prevention: P102: Keep out of reach of children.

	P103:	Read label before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P261:	Avoid breathing dust, mist, or vapors.
	P264:	Wash thoroughly after handling.
	P271:	Use only outdoors or in a well-ventilated area.
	P272:	Contaminated work clothing should not be allowed out of the workplace.
	P273:	Avoid release to environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P302+P352:	IF ON SKIN: Wash with plenty of water.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364:	Take off contaminated clothing and wash before re-use.
	P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P308+P313:	If exposed or concerned: Call a poison center/doctor.
Storage:	P391:	Collect spillage.
	P403:	Store in a well-ventilated place.
	P405:	Store locked up.
	P411:	Store between 45-90°F (7-32°C).
Disposal:	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

Hardener (Black Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Acute Toxicity, Dermal	Category 4	H312: Harmful in contact with skin
	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns
	Serious Eye Damage/Irritation	Category 1	H318: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
	Reproductive Toxicity	Category 2	H361: Suspected of damaging fertility
	Carcinogenicity	Category 2	H351: Suspected of causing cancer
	STOT, Repeated Exposure	Category 2	H373: May cause damage to organs through prolonged and repeated exposure
Environmental Hazards:	Acute Aquatic Hazard	Category 1	H400: Very toxic to aquatic life
	Chronic Aquatic Hazard	Category 1	H410: Very toxic to aquatic life with long lasting effects

Main Symptoms: Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. Long term exposure may cause chronic effects.

GHS Label Elements



Contains:	Ground Limestone, Benzyl Alcohol, 2-piperazin-1-ylethylamine, Bisphenol-A
Signal Word:	DANGER!
Hazard Statements:	H312: Harmful in contact with skin. H314: Causes severe skin burns and eye damage. H318: Causes serious eye damage. H317: May cause an allergic skin reaction. H361: Suspected of damaging fertility or the unborn child.

	H351:	Suspected of causing cancer.
	H373:	May cause damage to organs (nasal cavity) through prolonged or repeated exposure.
	H400:	Very toxic to aquatic life.
	H410:	Very toxic to aquatic life with long lasting effects.
Precautionary Statements:		
Prevention:	P102:	Keep out of reach of children.
	P103:	Read label before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P210:	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
	P260:	Do not breathe dust, mist, or vapor.
	P264:	Wash thoroughly after handling.
	P270:	Do not eat, drink, or smoke when using this product.
	P271:	Use only outdoors or in a well-ventilated area.
	P272:	Contaminated clothing should not be allowed out of the workplace.
	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P301+P330+P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P310:	Immediately call a POISON CENTER/doctor.
	P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P363:	Wash contaminated clothing before reuse.
	P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation occurs: Get medical advice/attention.
	P308+P313:	If exposed or concerned: Get medical advice/attention.
Storage:	P391:	Collect Spillage.
	P403:	Store in a well-ventilated place.
	P405:	Store locked up.
	P411:	Store between 45-90°F (7-32°C).
Disposal:	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

Hazards Not Otherwise Classified (HNOC)

The above hazards are for the uncured component of SET. Upon combination of the two components, an innocuous solid which does not present any immediate hazards is formed. Upon grinding or cutting the cured product, the following hazards may apply. Ensure good work practice and use of personal protective equipment as needed to control exposure to processing dust.



Chronic Health

Health Hazard:	Carcinogenicity	Category 1A
OSHA Hazard:	Combustible Dust	
Hazard Statement:	May cause cancer. Can form explosive air-dust mixtures, avoid creating dust.	
Precautionary Statement:	Do not breathe dust. Do not allow dust to build up on surfaces.	

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classification: Global Harmonized System Classifications

The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

SET® Anchoring Adhesive

SAFETY DATA SHEET

Resin (White Side)

Chemical Name	Weight %	CAS Number	EC Number
Bisphenol-A Based Epoxy Resin Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, Aquatic Chronic 2: H411	30-50	25068-38-6	500-033-5
Phenolic Novolac Resin Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, Aquatic Chronic 2: H411	40-70	28064-14-4	608-164-0
Butyl Glycidyl Ether Classifications: Flam. Liq. 3: H226, Acute Tox. 4: H302+H332, Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, GCM 2: H341, Carc. 2: H351, STOT SE 3: H335, Aquatic 3: H402+H412	1-5	2426-08-6	219-376-4
Titanium Dioxide Classifications: Carc. 2: H351	1-5	13463-67-7	236-675-5

Hardener (Black Side)

Chemical Name	Weight %	CAS Number	EC Number
Ground Limestone Classifications: Skin Irrit. 2: H315	20-40	1317-65-3	215-279-6
Benzyl Alcohol Classifications: Acute Tox. 4: H302+H332	1-15	100-51-6	202-859-9
2-Piperazin-1-ylethylamine Classifications: Acute Tox. 4: H302+H312, Skin Corr. 1: H314, Skin Sens. 1: H317, Aquatic 3: H402+H412	1-15	140-31-8	205-411-0
Bisphenol-A Classifications: Skin Corr. 1: H314, Eye Corr. 1: H318, Repr. 2: H361, STOT SE 3: H335	1-10	80-05-7	201-245-8
Nonyl Phenol Classifications: Acute Tox. 4: H302, Skin Corr. 1: H314, Repr. 2: H361, Aquatic 1: H400+H410	1-5	84852-15-3	284-325-5
Furfuryl Alcohol Classifications: Acute Tox. 3: H301+H311+H331, Eye Irrit. 2: H319, Carc. 2: H351, STOT SE 3: H335, STOT RE 2: H373	1-5	98-00-0	202-626-1
Benzyl dimethylamine Classifications: Flam. Liq. 3: H226, Acute Tox. 4: H302+H312+H332, Skin Corr. 1: H314, Aquatic 3: H402+H412	1-5	103-83-3	203-149-1
Triethylenetetramine Classifications: Acute Tox. 4: H312, Skin Corr. 1: H314, Skin Sens. 1: H317, Aquatic Chronic 3: H412	< 5	112-24-3	203-950-6
p-tert-butylphenol Classifications: Skin Irrit. 2: H315, Eye Corr. 1: H318, Repr. 2: H361, STOT SE 3: H335, Aquatic Chronic 2: H411	< 5	98-54-4	202-679-0
Crystalline Silica, Quartz Classifications: Carc. 1A: H350, STOT RE 1: H372	< 1	14808-60-7	238-878-4
Carbon Black Classifications: Carc. 2: H351	< 1	1333-86-4	215-609-9

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

Eye Contact:	Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, consult a physician immediately.
Skin Contact:	Remove contaminated clothing and product, immediately wash affected area with soap and water. Chemical burns must be treated by a physician.
Ingestion:	Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. Consult a physician immediately.
Inhalation:	Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, consult a physician.

Most Important Symptoms

Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. Permanent eye damage, including blindness, can result. Rash/dermatitis. May cause severe irritation or burns to the gastrointestinal tract and respiratory system.

5. Fire-Fighting Measures

Suitable Extinguishing Media:	Extinguish with foam, carbon dioxide, dry powder, or water fog.
Additional Information:	None known.
Hazards during Fire-Fighting:	Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C). Irritating and toxic gases/fumes may be released during a fire. Water run-off can cause environmental damage. Do not allow run-off from fire-fighting to enter drains or water courses.
Fire-Fighting Procedures:	Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers by flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Non-emergency personnel: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

Small spills (uncured):	Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination. If desired, approved solvents, such as ketones (MEK, acetone, etc.), lacquer thinner, or adhesive remover can be used. Do NOT use solvents to clean adhesives from skin. Take appropriate precautions when handling flammable solvents. Solvents may damage surfaces to which they are applied.
Large spills (uncured):	Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water.
Cured Material:	Chip or grind off surface. The product contains components that are carcinogenic in respirable form. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Do not breathe dust, mist, or vapor. When using, do not eat, drink or smoke. Avoid contact with eyes, skin, and clothing. Pregnant women should not work with this product if there is risk of exposure. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Storage

Full Unused Cartridges: Store away from incompatible materials (See Section 10 of the SDS). Keep in original container. Keep container tightly closed. Store in a dry, well-ventilated place out of direct sunlight between 45-90°F (7-32°C). Keep away from heat and sources of ignition. Protect container from physical damage. Keep out of reach of children.

Partially Used Cartridges: To store partially used cartridge, temporarily replace cap or leave hardened nozzle in place. To re-use, attach new nozzle. Do not try to dispense after adhesive hardens in nozzle. CAUTION: Adhesive will start to gel in the nozzle. Adhesive will gel faster at higher temperatures. Material under pressure can blowout the back of the cartridge if the adhesive in the nozzle hardens. Use only an appropriate Simpson Strong-Tie® mixing nozzle in accordance with Simpson Strong-Tie instructions. Modification or improper use of mixing nozzle may impair adhesive performance. Keep out of reach of children.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure: Wear appropriate personal protective equipment.
Eye Protection: Wear chemical splash goggles or safety glasses with side shield.
Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection: Wear long sleeve shirt/long pants and other clothing as required to minimize contact.
Respirator Protection: The use of a respirator is not required during normal use of this product. If grinding or cutting cured product, the use of an approved respirator is recommended.
General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

When using indoors good general ventilation should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station.

Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Triethylenetetramine* (CAS 112-24-3)	N/E	N/E	6 mg/m ³ 1 ppm
Quartz (CAS 14808-60-7)	$\frac{10}{\%SiO_2 + 2} \text{ mg/m}^3$	0.025 mg/m ³ (respirable)	0.05 mg/m ³ (respirable)
Limestone (CAS 1317-65-3)	5 mg/m ³ (Respirable) 15 mg/m ³ (Total dust)	N/E	5 mg/m ³ (respirable) 10 mg/m ³ (total dust)
Benzyl Alcohol (CAS 100-51-6)	5 mg/m ³ (TWA)	N/E	5 mg/m ³ (STEL) 10 ppm
Furfuryl alcohol* (CAS 98-00-0)	200 mg/m ³	40 mg/m ³ (TWA) 60 mg/m ³ (STEL)	40 mg/m ³ (TWA) 60 mg/m ³ (STEL)
Butyl Glycidyl Ether (CAS 2426-08-6)	270 mg/m ³ 50 ppm	3 ppm	30 mg/m ³ (ceiling) 5.6 ppm (ceiling)
Titanium Dioxide (CAS 13463-67-7)	5 mg/m ³ (respirable) 15 mg/m ³ (total dust)	10 mg/m ³	N/E
Carbon Black (CAS 1333-86-4)	3.5 mg/m ³	3 mg/m ³	0.1 mg/m ³

*Skin Designation: Material can be absorbed through the skin.

9. Physical and Chemical Properties

Property	Resin	Hardener
Physical State:	Liquid, Paste	Liquid, Paste
Color:	White	Black
Odor:	Sweet	Ammonia
pH:	6.9	10.6
Flammability limit – lower %:	No data	No data
Flammability limit – upper %:	No data	No data
Vapor Pressure:	Non-volatile	No data
Vapor Density:	No data	No data
Solubility:	Insoluble in water	Slightly soluble in water
Freezing/Melting Point:	No data	No data
Boiling Point:	> 500 °F (>260 °C)	No data
Flash Point:	250 °F (121 °C) Open Cup	198 °F (92.2 °C) Open Cup
Evaporation Rate:	No data	No data
Decomposition Temperature:	No data	No data
Specific Gravity:	1.21 at 72°F (22°C)	1.23 at 72°F (22°C)
VOC (after cure):	6 g/L	6 g/L
Kow:	No data	No data
Viscosity:	No data	No data

10. Stability and Reactivity

Resin (White Side)

Reactivity: This product is stable and non-reactive under normal conditions.
Chemical Stability: Stable under normal storage conditions.
Condition to Avoid: High heat and open flame.
Substances to Avoid: Oxidizing agents, acids, organic bases, and amines.
Hazardous Reactions: Hazardous polymerization does not occur.
Decomposition Products: Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

Hardener (Black Side)

Reactivity: This product is stable and non-reactive under normal conditions.
Chemical Stability: Stable under normal storage conditions.
Condition to Avoid: High heat and open flame.
Substances to Avoid: Strong oxidizing agents. Strong acids.
Hazardous Reactions: Hazardous polymerization does not occur.
Decomposition Products: Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion: Corrosive material; causes severe irritation or burns to the gastrointestinal tract and respiratory tract.
Inhalation: If this material is heated or misted, coughing and mild, irritation may occur. Do not inhale dust from cutting/grinding cured product.
Skin contact: Causes severe skin burns. May cause an allergic skin reaction. Harmful in contact with skin.
Eye contact: Causes serious eye damage.
Symptoms: Burns, redness, itching, tearing, swelling, and blurred vision. Rash/dermatitis. Severe irritation or burns to the gastrointestinal tract and respiratory system. Shortness of breath, discomfort in chest, or coughing.

Information on Toxicological Effects

Acute Effects

Toxicity: Harmful in contact with skin.

Product	Species	Test Result
SET Resin Mixture	Acute, Oral, LD50	Rat > 5000 mg/kg
	Acute, Dermal, LD50	Rabbit > 2000 mg/kg
SET Hardener Mixture	Acute, Oral, LD50	Rat > 5000 mg/kg

Component	Species	Test Result
Bisphenol-A Based Epoxy Resin (CAS 25068-38-6)	Acute, Oral, LD50	Rat 11400 mg/kg
	Acute, Dermal, LD50	Rabbit 2000 mg/kg
Titanium Dioxide (CAS 13463-67-7)	Acute, Oral, LD50	Rat > 10000 mg/kg
	Acute, Inhalation, LC50	Rat > 6.82 mg/l
Butyl Glycidyl Ether (CAS 2426-08-6)	Acute, Oral, LD50	Rat 1660 mg/kg
	Acute, Dermal, LD50	Rat > 2150 mg/kg
	Acute, Inhalation, LC50	Rat > 18.64 mg/l, 4 hours
Benzyl Alcohol (CAS 100-51-6)	Acute, Oral, LD50	Rat 1230 mg/kg
	Acute, Dermal, LD50	Rabbit 2000 mg/kg
	Acute, Inhalation, LC50	Rat > 4.18 mg/l, 4 hours
2-Piperazin-1-ylethylamine (CAS 140-31-8)	Acute, Oral, LD50	Rat 2180 mg/kg
	Acute, Dermal, LD50	Rabbit 880 mg/kg

SET® Anchoring Adhesive
SAFETY DATA SHEET



Component	Species	Test Result
Bisphenol-A (CAS 80-05-7)	Acute, Oral, LD50	Rat 3250 mg/kg
	Acute, Dermal, LD50	Rabbit 3600 mg/kg
Nonyl Phenol (CAS 84852-15-3)	Acute, Oral, LD50	Rat 1300 mg/kg
	Acute, Dermal, LD50	Rabbit 2033 mg/kg
Furfuryl Alcohol (CAS 98-00-0)	Acute, Oral, LD50	Rat 177 mg/kg
	Acute, Dermal, LD50	Rat 3825 mg/kg
	Acute, Inhalation, LC50	Rat 233 ppm, 4 hours
Benzyldimethylamine (CAS 103-83-3)	Acute, Oral, LD50	Rat 265 mg/kg
	Acute, Dermal, LD50	Rabbit 1660 mg/kg
	Acute, Inhalation, LC50	Rat 2.05 mg/l, 4 hours
Triethylenetetramine (CAS 112-24-3)	Acute, Oral, LD50	Rat 1716 mg/kg
	Acute, Dermal, LD50	Rabbit 1465 mg/kg
p-tert-butylphenol (CAS 98-54-4)	Acute, Oral, LD50	Rat 2951 mg/kg
	Acute, Dermal, LD50	Rabbit 2288 mg/kg
Crystalline Silica, Quartz (CAS 14808-60-7)	Acute, Oral, LD50	Rat 22500 mg/kg

Skin corrosion/irritation: Causes skin irritation and severe skin burns.
Eye damage/eye irritation: Causes serious eye irritation and damage.
Respiratory sensitization: No data available.
Skin sensitization: May cause an allergic skin reaction.
Aspiration hazard: No data available.
Specific target organ toxicity
Single exposure: No data available.

Chronic Effects

Germ cell mutagenicity: SET Resin contains a component that is suspected of causing genetic defects.
Carcinogenicity: This product contains components that are suspected of being carcinogenic. The product also contains components which are considered carcinogens only in their respirable form. Due to the nature of this product, exposure to respirable particles is likely only when grinding or cutting cured product. Ensure good work practice and use of personal protective equipment as needed to control exposure.

Reproductive toxicity: SET Hardener contains components which are suspected of damaging fertility or the unborn child.

Specific target organ toxicity
Repeated exposure: May cause damage to organs (nasal cavity) through prolonged or repeated exposure.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Quartz (CAS 14808-60-7)	< 1	1	KNOWN	A2	CA65
Titanium Dioxide (CAS 13463-67-7)	1-5	2B	---	---	CA65
Carbon Black (CAS 1333-86-4)	< 1	2B	---	---	CA65
Bisphenol-A (CAS 80-05-7)	1-10	---	---	---	CA65
Nonyl Phenol (CAS 84852-15-3)	1-5	---	---	---	Limited evidence of reproductive toxicity (NOAEL >2000 ppm)

IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 - Not classifiable as to carcinogenicity 4 - Probably not carcinogenic
NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen
ACGIH - A1 - Confirmed carcinogen A2 - Suspected carcinogen A3 - Animal carcinogen A4 - Not classified A5 - Not suspected
CA65 - California Prop 65

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. SET Resin is not classified as an environmental hazard. SET Hardener is classified as very toxic to aquatic life, with long lasting effects. Avoid release to the environment.

Supporting Data

Component	Species	Test Result
SET Resin Mixture		
Aquatic Acute , Fish, LC50	Fish	707.11 mg/l, 96 hours
Aquatic Acute , Crustacea, EC50	Daphnia magna	324.87 mg/l, 48 hours
Aquatic Acute , Algae, EC50	Algae	>1000 mg/l, 72 hours

Component	Species	Test Result
Butyl Glycidyl Ether (CAS 2426-08-6)		
Aquatic , Crustacea, EC50	Daphnia magna	3.9 mg/l, 48 hours
Bisphenol-A Based Epoxy Resin (CAS 25068-38-6)		
Aquatic , Fish, LC50	Fish	1.3 mg/l, 96 hours
Aquatic , Crustacea, EC50	Daphnia magna	2.1 mg/l, 48 hours
Aquatic , Algae, EC50	Algae	> 11 mg/l, 72 hours
2-Piperazin-1-ylethylamine (CAS 140-31-8)		
Aquatic , Fish, LC50	Fathead minnow	1950-2460 mg/l, 96 hours
Aquatic , Crustacea, EC50	Invertebrates	58 mg/l, 48 hours
Aquatic , Algae, EC50	Algae	> 1000 mg/l, 72 hours
Benzyl Alcohol (CAS 100-51-6)		
Aquatic , Fish, LC50	Bluegill	10 mg/l, 96 hours
Aquatic , Crustacea, EC50	Daphnia magna	23 mg/l, 48 hours
Aquatic , Algae, EC50	Algae	700 mg/l, 72 hours
Nonyl Phenol (CAS 84852-15-3)		
Aquatic , Fish, LC50	Winter flounder	0.017 mg/l, 96 hours
Aquatic , Crustacea, EC50	Clam	0.0379 mg/l, 48 hours
Bisphenol-A (CAS 80-05-7)		
Aquatic , Fish, LC50	Fathead minnow	3.6-5.4 mg/l, 96 hours
Aquatic , Crustacea, EC50	Daphnia magna	9.2-11.4 mg/l, 48 hours
Furfuryl Alcohol (98-00-0)		
Aquatic , Fish, LC50	Fathead Minnow	32 mg/l, 96 hours
Benzyl dimethylamine (CAS 103-83-3)		
Aquatic , Fish, LC50	Fathead Minnow	35.8-39.9 mg/l, 96 hours
p-tert-butylphenol (CAS 98-54-4)		
Aquatic , Fish, LC50	Fathead minnow	5.14 mg/l, 96 hours
Aquatic , Crustacea, EC50	Daphnia magna	4.8 mg/l, 48 hours

Persistence and degradability: This product is not expected to be readily biodegradable.

Bioaccumulative potential: No data available for this product.

Chemical	Log Kow	BCF	Bioaccumulation Potential
Butyl Glycidyl Ether (CAS 2426-08-6)	0.63	---	low
BPA Epoxy Resin (CAS 25068-38-6)	2.64-3.78	3-31	low
Phenolic Novolac Resin (CAS 28064-14-1)	3	---	low
2-Piperazin-1-ylethylamine (CAS 140-31-8)	-1.48	---	---
p-tert-butylphenol (CAS 98-54-4)	---	20.43	---
Bisphenol-A (CAS 80-05-7)	3.32	5.1-73.4	low

SET® Anchoring Adhesive
SAFETY DATA SHEET



Chemical	Log Kow	BCF	Bioaccumulation Potential
Nonyl Phenol (CAS 84852-15-3)	5.71	---	medium
Benzyl Alcohol (CAS 100-51-6)	1.1	---	---
Triethylenetetramine (CAS 112-24-3)	-1.66 - -1.4	---	---
Furfuryl Alcohol (CAS 98-00-0)	0.3	---	---

Mobility in soil: This product is non-volatile.

Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Consideration

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal of Cured Product: Chip or grind off surface. Solid material does not need special disposal consideration.

14. Transportation Information

Check limited quantity regulations prior to shipping. SET cartridges may qualify for LQ shipping exemptions.

	Resin (White Side)	Hardener (Black Side)
UN number:	UN3082	UN2735
UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant	AMINES, LIQUID, CORROSIVE, N.O.S. (Aminoethylpiperazine, Nonylphenol), 8, III, Marine Pollutant
Precautions:	Marine Pollutant	Marine Pollutant
Required Labels:	9	8
ERG Code (IATA):	9L	8L
EmS (IMDG):	F-A, S-F	F-A, S-B

Additional Information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
This substance/mixture is not intended to be transported in bulk

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):
Nonyl Phenol (CAS 84852-15-3) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4):
1-Butanol (CAS 71-36-3) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:					
	Immediate	Delayed	Fire	Pressure	Reactivity
Resin	Yes	Yes	No	No	No
Hardener	Yes	Yes	No	No	No

SET® Anchoring Adhesive

SAFETY DATA SHEET

SARA 302 Extremely hazardous substance: No
 SARA 311/312 Hazardous chemical: Yes
 SARA 313 (TRI reporting):

Chemical	CAS Number	% In Blend (approx.)
1-Butanol	71-36-3	< 0.1
Nonyl Phenol	84852-15-3	1-5
Bisphenol A	80-05-7	1-10

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or reproductive harm.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Quartz (CAS 14808-60-7)	< 1	1	KNOWN	A2	CA65 (Carcinogenic)
Titanium Dioxide (CAS 13463-67-7)	1-5	2B	---	---	CA65 (Carcinogenic)
Carbon Black (CAS 1333-86-4)	< 1	2B	---	---	CA65 (Carcinogenic)
Bisphenol-A (CAS 80-05-7)	1-10	---	---	---	CA65 (Reproductive)

IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic
 NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen
 ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected
 CA65 – California Prop 65

US State Right-To-Know Lists

Chemical	Massachusetts RTK	New Jersey Work and Community RTK Act	Pennsylvania Worker and Community RTK Law	Rhode Island RTK	Maine CHC
Butyl Glycidyl Ether (CAS 2426-08-6)	Listed	Listed	Listed	Listed	
Titanium Dioxide (CAS 13463-67-7)	Listed	Listed	Listed		
Carbon Black (CAS 1333-86-4)	Listed	Listed	Listed		Listed
2-Piperazin-1-ylethylamine (CAS 140-31-8)	Listed	Listed	Listed		
Benzyl dimethylamine (CAS 103-83-3)		Listed			
Nonyl Phenol (CAS 84852-15-3)					Listed
Bisphenol-A (CAS 80-05-7)	Listed	Listed	Listed		
Benzyl Alcohol (CAS 100-51-6)	Listed		Listed		
Triethylenetetramine (CAS 112-24-3)	Listed	Listed	Listed		
Furfuryl Alcohol (CAS 98-00-0)	Listed	Listed	Listed		
Ground Limestone (CAS 1317-65-3)	Listed	Listed	Listed		
Quartz (CAS 14808-60-7)	Listed	Listed	Listed		Listed

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

REACH Registered Substances			
Chemical	CAS Number	EC Number	Index Number
BPA Based Epoxy Resin	25068-38-6	500-033-5	603-074-00-8
Butyl Glycidyl Ether	2426-08-6	219-376-4	603-039-00-7
2-Piperazin-1-ylethylamine	140-31-8	205-411-0	612-105-00-4
Benzyl dimethylamine	103-83-3	203-149-1	612-074-00-7
Nonyl Phenol	84852-15-3	284-325-5	601-053-00-8
p-tert-butylphenol	98-54-4	202-679-0	604-090-00-8
Bisphenol-A	80-05-7	201-245-8	604-030-00-0
Benzyl Alcohol	100-51-6	202-859-9	603-057-00-5
Triethylenetetramine	112-24-3	203-950-6	612-059-00-5
Furfuryl Alcohol	98-00-0	202-626-1	603-018-00-2

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL).
China	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).
Europe	One or more components of this product are not included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are not exempt from listing.
Japan	All components of this product are listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	All components of this product are included on the Existing Chemicals List (ECL).
New Zealand	All components of this product are listed on the New Zealand Inventory.
Philippines	All components in this product are listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.


16. Other Information

Date Prepared or Revised: August 2016
Supersedes: September 2014

Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com

Additional Resin (White Side) Classifications

NFPA Ratings



HMIS Rating


HEALTH	2	PHYSICAL	0
FLAMMABILITY	1	PPE	B

SET® Anchoring Adhesive

SAFETY DATA SHEET

Additional Hardener (Black Side) Classifications

NFPA Ratings



HMIS Rating

HEALTH	3	PHYSICAL	0
FLAMMABILITY	1	PPE	B

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HPR:	Hazardous Product Regulations (Canada)
DOT:	Department of Transportation (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Full Text of H – Phrases Under Section 3

H226:	Flammable liquid and vapor.
H301:	Toxic if swallowed.
H302:	Harmful if swallowed.
H311:	Toxic in contact with skin.
H312:	Harmful in contact with skin.
H314:	Causes severe skin burns and eye damage.
H315:	Causes skin irritation.
H317:	May cause an allergic skin reaction.
H318:	Causes serious eye damage.
H319:	Causes serious eye irritation.
H331:	Toxic if inhaled.
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation.
H341:	Suspected of causing genetic defects.
H350:	May cause cancer.
H351:	Suspected of causing cancer.
H361:	Suspected of damaging fertility or the unborn child.
H372:	Causes damage to organs through prolonged and repeated exposure.

SET[®] Anchoring Adhesive

SAFETY DATA SHEET

- H373:** May cause damage to organs through prolonged and repeated exposure.
- H400:** Very toxic to aquatic life.
- H402:** Harmful to aquatic life.
- H410:** Very toxic to aquatic life with long lasting effects.
- H411:** Toxic to aquatic life with long lasting effects.
- H412:** Harmful to aquatic life with long lasting effects.

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2016 Simpson Strong-Tie Company Inc.

Internal

FOR INTERNAL USE ONLY

SET Resin:	SET Hardener:
XCOM3B – 50% Cartridge	XCOM3A – 50% Cartridge
	XCORR – 50% Cartridge